



## Plastic carrier rollers KUT 100

Plastic pipe Ø 20, 30, 40, 50, 63

- **Axle:** Steel, bright-drawn ST 37 K, axle end with external thread, internal thread, spring axle or spanner flat.
- **Bearing:** Thermoplastic bearing with one row of balls.
- Please specify the exact model when ordering: Roller Ø, axle Ø, axle type, roller length (RL), fitting length (EL) and axle length (AL).
- **Order example:**  
KUT 100/50x1.5/KB/A10/M10 EL=500mm bzw.  
KUT 100/63x3/KB/A12/SW10 EL=600mm

- **Use:** gravity carrier roller, light running, light non-driven roller conveyors for in-house employment, higher degree of running smoothness than TRG

These carrier rollers are also available in stainless steel (stainless steel bearing balls and axle).

Prices on request

For standard lengths see page F 7

Order No.	Precision tubing	Axle Ø										
	mm D x W	mm A	mm M	mm G	mm F	mm IG	mm F	mm G	mm F	mm SW	mm G	mm F
KUT 100/20x1.5/KB/A06	20 x 1.5	6	M6	15	7.5	-	-	8	2.5	-	-	-
KUT 100/20x1.5/KB/A08	20 x 1.5	8	M8	15	9	-	-	10	2.5	-	-	-
KUT 100/30x1.8/KB/A06	30 x 1.8	6	M6	15	7.5	-	-	8	2.5	-	-	-
KUT 100/30x1.8/KB/A08	30 x 1.8	8	M8	15	9	-	-	10	2.5	-	-	-
KUT 100/30x1.8/KB/A10	30 x 1.8	10	M10	15	8.5	M6	2.5	10	2.5	8	10	2.5
KUT 100/40x2.3/KB/A08	40 x 2.3	8	M8	15	9	-	-	10	2.5	-	-	-
KUT 100/40x2.3/KB/A10	40 x 2.3	10	M10	15	8.5	M6	2.5	10	2.5	8	10	2.5
KUT 100/50x2.8/KB/A08	50 x 2.8	8	M8	15	10	-	-	10	3.5	-	-	-
KUT 100/50x2.8/KB/A10	50 x 2.8	10	M10	15	9.5	M6	3.5	10	3.5	8	10	3.5
KUT 100/50x2.8/KB/A12	50 x 2.8	12	M12	15	10.5	M8	3.5	12	3.5	8/10	10	3.5
KUT 100/63x3/KB/A08	63 x 3.0	8	M8	15	10	-	-	10	3.5	-	-	-
KUT 100/63x3/KB/A10	63 x 3.0	10	M10	15	9.5	M6	3.5	10	3.5	8	10	3.5
KUT 100/63x3/KB/A12	63 x 3.0	12	M12	15	10.5	M8	3.5	12	3.5	8/10	10	3.5