

# locking castors // up to 1,200 kg



## Features:

- FSR plate
- polyamide 6 wheels with plain bearing
- resistant to fracturing even at heavy loads

## Series FSR50-600










- housing made of power-coated aluminum
- fastening components are made from C45
- locking foot made of aluminum/rubber

## Series FSR800-1300

- housing made of cast iron
- locking foot made of steel/plastic

## Series FSR RF

- height is not adjustable
- with wheel brake

locking castors									
	wheel ø mm	wheel width mm	installation height, rolling mm	extended installation height mm	projection, swivel castor mm	plate size mm	hole spacing mm	bolt hole ø mm	load-carrying capacity kg
FSR-300-3 ID: 0016579	50	22	83	95	60	73 x 73	58 x 58	6.5	200
FSR-600-3 ID: 0016581	63	29	102	117	83.5	90 x 90	70 x 70	9	400
FSR-RF-600-3 ID: 0029635	60	55	90		25	90 x 90	70 x 70	9.5	800
FSR-RF-800-3 ID: 0029636	75	55	108		25	90 x 90	70 x 70	9.5	1,000
FSR-1000-3 ID: 0016574	72	31	120	138	90	95 x 95	70 x 70	11	700
FSR-RF-1000-3 ID: 0029637	75	55	110	160	65.5	95 x 95	70 x 70	9.5	1,000
FSR-1300-3 ID: 0016576	72	31	121	139	89.5	95 x 95	70 x 70	11	900
FSR-1800-3 ID: 0016577	92	54	130	155	115	100 x 100	70 x 70	13	1,200