



TORWEGGE wheel conveyors

- **TORWEGGE wheel conveyors with:**
 Plastic rollers 2300/48/6
 Steel rollers 2200/48/6
 Multi-directional wheels AWR 48
 For replacement rollers, see pages F 34 and F 35.
- **Or on request with rubber rollers 2300/54/8GU with a pitch of 75 mm.**
- For transporting light material with a smooth and sturdy base via gravitational force.
- **Frame:** U-profile 20/70/20 mm, galvanized, with screwed-in transverse bars. Axles also supported by central struts.
- **Bends:** Inside radius 800 mm. Different radii are also available on request.

The wheel conveyors are equipped with galvanized quick connectors as standard. These enable the tracks to be expanded at any time. Other widths and lengths available on request. Custom-made specifications are available on request.

PVC edge protection available on request.

Ball caster tables for filtering as rotary and distributor table.
 The material being conveyed on ball caster tables must have a sturdy, smooth base. Please indicate the weight and size of the material to be conveyed. You will then receive our quote.

Also available with PU rollers 2400/48/8-K

Wheel conveyors with plastic rollers 2300/48/6

Total width mm	Track width mm	Spacing mm	Order No.	Wheel conveyors			Bends		
				Ident. No.	Ident. No.	Ident. No.	Please specify 45° or 90° when ordering!		
				1000 mm	2000 mm	3000 mm	Order No.	Ident. No.	Ident. No.
								45°	90°
340	300	50	203050 KU x	0011406	0011407	0011408	-	-	-
340	300	75	203075 KU x	0011409	0011410	0011411	213075 KU	0011498	0011499
340	300	100	203100 KU x	0011412	0011413	0011414	-	-	-
340	300	125	203125 KU x	0011415	0011416	0011417	213125 KU	0011500	0011505
440	400	50	204050 KU x	0011424	0011425	0011426	-	-	-
440	400	75	204075 KU x	0011427	0011428	0011429	214075 KU	0011506	0011507
440	400	100	204100 KU x	0011430	0011431	0011432	-	-	-
440	400	125	204125 KU x	0014433	0014434	0014435	214125 KU	0011508	0011509
540	500	50	205050 KU x	0011442	0011443	0011444	-	-	-
540	500	75	205075 KU x	0011445	0011446	0011447	215075 KU	0011510	0011511
540	500	100	205100 KU x	0011448	0011449	0011450	-	-	-
540	500	125	205125 KU x	0011451	0011452	0011453	215125 KU	0011510	0011513
640	600	50	206050 KU x	0011460	0011461	0011462	-	-	-
640	600	75	206075 KU x	0011463	0011464	0011465	216075 KU	0011514	0011515
640	600	100	206100 KU x	0011466	0011467	0011468	-	-	-
640	600	125	206125 KU x	0011469	0011470	0011471	216125 KU	216125	216126
840	800	50	208050 KU x	0011480	0011481	0011482	-	-	-
840	800	75	208075 KU x	0011483	0011484	0011485	218075 KU	0011518	0011519
840	800	100	208100 KU x	0011486	0011487	0011488	-	-	-
840	800	125	208125 KU x	0011489	0011490	0011491	218125 KU	0011520	0011521

Leaving technical changes!