

Series 237 Product Overview

Features:

- Low profile
- Large handle clearance in the open position.
- Available in stainless steel


Applications:

- Assembly
- Checking fixtures
- Welding


Also Available:

See page 7.1 for accessories  
Accommodates M10 or 3/8" spindle accessory

237-U  
Flanged Base  
U-Bar



237-USS<sup>①</sup>  
Flanged Base  
U-Bar, Stainless  
Steel




Note:  
Clamps shown with included accessories.

Series 237 Technical Information

Model	Max. Holding Capacity	Clamp Bar Opening(+10°)	Handle Opening (+10°)	Weight	Accessories (Supplied)	
					Spindle Assembly	Flanged Washers
237-U	3340 N [750 lbf]	93°	59°	0,73kg [1.60lb]	240208-M	235106
237-USS <sup>①</sup>	3780 N [850 lbf]				237943-M	235906

<sup>①</sup> This item is available upon request

Series 237 Holding Capacities



Model	X	X1	X2	Y	±HC1	±HC2	±EF(X1):AF	±EF(X2):AF
U	[0.81]	[1.75]	[4.50]	[5.25]	[750lbf.] 3340N	[290lbf.] 1290N	6:1	2:1
USS	20,6	44,5	114,3	133,3	[850lbf.] 3780N	[330lbf.] 1470N		

Dimensions shown "mm [inch]" ± HC = Holding Capacity, EF = Exerting Force, AF = Applied Force  
Refer to page 15.4 for additional information.

## Series 237 Standard Clamp Dimensions -U/-USS

**237-U**  
Flanged Base  
U-Bar

