



Vollgummi-Rollen

50 - 385 kg

Swivel castors

Wheel series

522:

- ▶ Steel plate wheel centre **with roller bearing**
- ▶ Solid rubber running surface, odourless, black, approx. 80° - 85° Shore hardness A
- ▶ Floor contact staining can occur with these tyres



Order No.

	mm	mm	mm	mm	mm	mm	mm	kg
LI/522/080/R	80	25	100	36	105 x 80	80 x 60	9	50
LI/522/100/R	100	30	125	38	105 x 80	80 x 60	9	70
LI/522/125/R	125	38	155	38	105 x 80	80 x 60	9	100
LI/522/140/R	140	37	173	46	115 x 85	80 x 60	9	120
LI/522/160/R	160	40	190	52	135 x 110	105 x 80	11	135
LI/522/180/R	180	50	210	53	135 x 110	105 x 80	11	170
LI/522/200/R	200	50	235	54	135 x 110	105 x 80	11	205
LI/522/225/R	225	55	250	53	140 x 110	105 x 80	11	250
LI/522/250L/R	250	60	290	66	135 x 110	105 x 80	11	275
LI/522/280/R	280	70	320	72	200 x 160	160 x 120	14	385

50 - 385 kg

Swivel castors with double



Order No.

	mm	mm	mm	mm	mm	mm	mm	kg
LI/522/080/RDS-N	80	25	100	36	105 x 80	80 x 60	9	50
LI/522/100/RDS-N	100	30	125	38	105 x 80	80 x 60	9	70
LI/522/125/RDS-N	125	38	155	38	105 x 80	80 x 60	9	100
LI/522/140/RDS-V	140	37	173	46	115 x 85	80 x 60	9	120
LI/522/160/RDS-N	160	40	190	52	135 x 110	105 x 80	11	135
LI/522/180/RDS-N	180	50	210	53	135 x 110	105 x 80	11	170
LI/522/200/RDS-N	200	50	235	54	135 x 110	105 x 80	11	205
LI/522/225/RDS-N	225	55	250	53	140 x 110	105 x 80	11	250
LI/522/250L/RDS-V	250	60	290	66	135 x 110	105 x 80	11	275
LI/522/280/RDS-V	280	70	320	72	200 x 160	160 x 120	14	385


50 - 385 kg

Fixed castors



Order No.

	mm	mm	mm	mm	mm	mm	mm	kg
BI/522/080/R	80	25	100	-	102 x 87	80 x 60	9	50
BI/522/100/R	100	30	125	-	102 x 87	80 x 60	9	70
BI/522/125/R	125	38	155	-	102 x 87	80 x 60	9	100
BI/522/140/R	140	37	173	-	115 x 85	80 x 60	9	120
BI/522/160/R	160	40	190	-	135 x 114	105 x 80	11	135
BI/522/180/R	180	50	210	-	135 x 110	105 x 80	11	170
BI/522/200/R	200	50	235	-	135 x 114	105 x 80	11	205
BI/522/225/R	225	55	250	-	140 x 110	105 x 80	11	250
BI/522/250L/R	250	60	290	-	135 x 114	105 x 80	11	295
BI/522/280/R	280	70	320	-	195 x 160	160 x 120	14	385



Housing series LI:

- ▶ Standard steel plate housing, galvanised
- ▶ Fork head with double ball bearing



You can find individual wheels from this series on page R 16