Chemical compatibility for drain covers, conical drain plugs and flexible barriers

Good behaviour to this chemical agents:

- ✓ methanol
- ✓ ammonia anhydrous
- ✓ butanol
- ✓ baric acid
- ✓ kerozene
- ✓ gazoline
- ✓ hexane
- ✓ naphtha
- ✓ aluminium salts
- ✓ mineral oil
- ✓ glycol ether
- ✓ formaldehyde
- ✓ propylene glycol
- ✓ barium salts
- ✓ jet fuel (JP-5)

Little swelling to this chemical agents:

- ✓ trichloroethylene
- ✓ diethylamine
- √ benzylalcohol
- ✓ toluene
- ✓ trichloroethane
- ✓ acetonitrile
- ✓ ethyl acetate
- ✓ carbon disulfide

Not compatible:

- ✓ acetone
- ✓ phenol
- ✓ sulfuric acid 50 %
- ✓ sulfuric acid 98 %
- ✓ hydrochloric acid 37 %
- ✓ hydrofluoric acid 48 %
- ✓ dichloromethane
- ✓ nitrobenzene
- ✓ dimethylformamide
- ✓ methylethylketone
- ✓ tetrahydrofuran

Tests results are given for your information only, we cannot be held responsible and guarantee cannot be applied in the event of faulty use, testing is recommended to check that the instructions for use and application conditions are suitable.