



|  |   |
|--|---|
| <b>Light source</b>                      | LED   |
| <b>Work equipment</b>                    | Without   |
| <b>Connected load</b>                    | 22 - 26 V; DC   |
| <b>Power consumption</b>                 | ca. 25 W  |
| <b>Luminous flux</b>                     | approx. 1.900 lm  |
| <b>Luminous efficiency <sup>1)</sup></b> | approx. 76 lm/W   |
| <b>Light type/-color</b>                 | Daylight  |
| <b>Colour temperatur</b>                 | approx. 5.600 K   |
| <b>Color rendering index</b>             | CRI ≥ 80  |
| <b>Light distribution</b>                | Direct; Symmetric   |
| <b>Beam angle</b>                        | 90°   |
| <b>Chromaticity tolerance LED</b>        | < 5 SDCM  |
| <b>Glare control</b>                     | optical film  |
| <b>Luminance (L65)</b>                   | ≤ 10.000 cd/m <sup>2</sup>  |
| <b>UGR class (4H 8H; EN 12464-1)</b>     | ≤ 25  |
| <b>System of protection/Class</b>        | IP 68 - 1 m / IPX9; III   |
| <b>Technology</b>                        | Two-stage switchable  |
| <b>Operation</b>                         | External  |
| <b>Housing</b>                           | Aluminium; Anodised; Aluminium coloured<br>anodised<br>Borosilicate |
| <b>Light source cover</b>                | Borosilicate  |
| <b>Mains lead</b>                        | Built-in plug; RSFPM 5/0.5 M  |
| <b>Design</b>                            | mounted version   |
| <b>Fastening</b>                         | Mounting rail; Tap hole 2xM6  |
| <b>Maximum ambient temperature</b>       | 60 °C   |
| <b>Decorative contrast side parts</b>    | Metallic silver   |
| <b>EAN</b>                               | 4013330016548   |
| <b>Weight without/incl. packaging</b>    | ca. 4,8 kg; 6,1 kg  |
| <b>Packaging dimensions</b>              | ca. 460 mm; 170 mm; 72 mm   |
| <b>Special features</b>                  | Light forming; Connection on the rear side; Eco mode                |

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g