



RSFM 4/0,05 P25-1

A50 | 100.0% Φ: 1450 lm




100 x 100 cm Φ: 1450 lm

Em: 484 lx
Emax: 661 lx
Emin: 304 lx



Φ: 1450 lm E | 0°



Light source	LED
Work equipment	Without
Connected load	20 - 28 V; DC
Power consumption	ca. 14 W
Luminous flux	approx. 1.450 lm
Luminous efficiency ¹⁾	approx. 103 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 5.000 K
Color rendering index	CRI ≥ 80
Light distribution	Wide beam; Direct; Symmetric
Beam angle	90°
Chromaticity tolerance LED	< 4 SDCM
Glare control	without
Luminance (L65)	≤ 42.000 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 25
System of protection/Class	IP 67; III
Technology	Switchable
Operation	External
Housing	Aluminium; Anodised; Aluminium coloured anodised Borosilicate; Clear
Light source cover	
Mains lead	Built-in plug; RSFM 4/0,05 P25-1
Design	mounted version
Fastening	L-angle; Clamp
Minimum ambient temperature	0 °C
Maximum ambient temperature	60 °C
EAN	4013330015527
Weight without/incl. packaging	ca. 0,8 kg; 1 kg
Dimensions (dimensional drawing)	A=540 mm
Packaging dimensions	ca. 595 mm; 90 mm; 85 mm
Special features	Suitable for higher ambient temperatures

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear

Surface-mounted luminaire MACH LED PLUS.forty MLAL 42 S

113691000-00801359

