



Light source	LED
Work equipment	Without
Connected load	16 - 32 V; DC
Power consumption	ca. 4,5 W
Luminous flux	approx. 590 lm
Luminous efficiency ¹⁾	approx. 118 lm/W
Light type/-color	Daylight
Colour temperatur	approx. 5.400 K
Color rendering index	CRI ≥ 80
Light distribution	Direct; approx. 93 %
Beam angle	120°
Chromaticity tolerance LED	< 5 SDCM
Glare control	without
Luminance (L65)	≤ 8.000 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 25
System of protection/Class	IP 67; III
Technology	Switchable
Operation	External
Housing	Polycarbonate (PC), clear
Light source cover	Polycarbonate (PC)
Mains lead	Built-in plug; QUICKON 3
Fastening	Lamp bracket (accessory)
Light output	D=307 mm
Side part	D with plug
Minimum ambient temperature	-25 °C
Maximum ambient temperature	40 °C
EAN	4013330083809
Weight without/incl. packaging	ca. 0,4 kg; 0,6 kg
Dimensions (dimensional drawing)	A=368 mm
Packaging dimensions	ca. 595 mm; 90 mm; 85 mm
Special features	Through-wired

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control g