



A80 ↓ 100.0% Φ: 600 lm



30 x 30 cm Φ: 600 lm

Em: 5010 lx
Emax: 28559 lx
Emin: 839 lx



0 10 20 30
Φ: 600 lm E ↓ 0°

Height (m)	Beam Diameter (m)	Light Intensity (lx)
0.25	0.039	126826
0.50	0.078	31708
0.75	0.12	14092
1.00	0.16	7927

Light source	LED
Work equipment	Without
Connected load	12 - 40 V; 12-28 V, AC and 12-40 V, DC; AC; DC
Power consumption	ca. 8 W
Luminous flux	approx. 600 lm
Luminous efficiency ¹⁾	approx. 75 lm/W
Light type/-color	Cold white
Colour temperatur	approx. 5.000 K
Color rendering index	CRI ≥ 80
Light distribution	Narrow-beam; Direct
Beam angle	10°
Chromaticity tolerance LED	< 4 SDCM
Glare control	Optics
Luminance (L65)	≤ 4.000 cd/m ²
UGR class (4H 8H; EN 12464-1)	≤ 16
System of protection/Class	IP 67; III
Technology	Switchable; Continuously dimmable
Operation	Push button
Housing	Aluminium; Anodised; Black
Light source cover	Borosilicate
Arm	Black
Mains lead	ca. 3,2 m; With free stranded wires
Fastening	Table clamp (accessory); Wall bracket (accessory); Screw-down flange
Maximum ambient temperature	40 °C
EAN	4013330088446
Weight without/incl. packaging	ca. 2 kg; 2,7 kg
Packaging dimensions	ca. 980 mm; 200 mm; 130 mm

¹⁾ For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear

Flexible-tube luminaire ROCIA.focus RFF 600/850/DS

113184000-00680272

