



<b>Light source</b>	LED
<b>Work equipment</b>	Electronic plug-in transformer
<b>Connected load</b>	100 - 240 V; AC; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 6 W
<b>Luminous flux</b>	approx. 460 lm
<b>Luminous efficiency <sup>1)</sup></b>	approx. 76 lm/W
<b>Light type/-color</b>	Cold white
<b>Colour temperatur</b>	approx. 5.000 K
<b>Color rendering index</b>	CRI ≥ 70
<b>Light distribution</b>	Wide beam; Direct
<b>Glare control</b>	Optics
<b>System of protection/Class</b>	IP 67; II with plug-in power supply, III without plug-in power supply
<b>Technology</b>	Switchable
<b>Operation</b>	Push button
<b>Housing</b>	Aluminium; Painted; Black
<b>Light source cover</b>	Borosilicate
<b>Arm</b>	Black
<b>Mains lead</b>	ca. 3 m; Mains plug; CEE 7/XVI; BS 1363 A; NEMA 1-15P
<b>Fastening</b>	Screw-down flange
<b>Maximum ambient temperature</b>	40 °C
<b>EAN</b>	4013330094898
<b>Weight without/incl. packaging</b>	ca. 1,7 kg; 2,6 kg
<b>Packaging dimensions</b>	ca. 930 mm; 180 mm; 130 mm
<b>Special features</b>	Flood

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear.