



**Light source**  
LED

**Work equipment**  
Without

**Connected load**  
Depending on the ballast; DC

**Power consumption**  
ca. 3 W

**Luminous flux**  
approx. 160 lm

**Luminous efficiency <sup>1)</sup>**  
approx. 53 lm/W

**Light type/-color**  
Daylight

**Colour temperatur**  
approx. 6.500 K

**Color rendering index**  
CRI ≥ 75

**Light distribution**  
Wide beam; Direct

**Glare control**  
without

**System of protection/Class**  
IP 67; III

**Operation**  
External

**Housing**  
Aluminium; Anodised; Jet black

**Light source cover**  
Borosilicate

**Arm**  
Black

**Mains lead**  
ca. 5 m; With free stranded wires

**Fastening**  
Table clamp (accessory); Wall bracket (accessory);  
Screw-down flange

**Maximum ambient temperature**  
25 °C

**EAN**  
4013330715496

**Weight without/incl. packaging**  
ca. 1,1 kg; 1,9 kg

**Packaging dimensions**  
ca. 980 mm; 200 mm; 130 mm

**Special features**  
Flood

LED

Without

Depending on the ballast; DC

ca. 3 W

approx. 160 lm

approx. 53 lm/W

Daylight

approx. 6.500 K

CRI ≥ 75

Wide beam; Direct

without

IP 67; III

External

Aluminium; Anodised; Jet black

Borosilicate

Black

ca. 5 m; With free stranded wires

Table clamp (accessory); Wall bracket (accessory);  
Screw-down flange

25 °C

4013330715496

ca. 1,1 kg; 1,9 kg

ca. 980 mm; 200 mm; 130 mm

Flood

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear.