



<b>Light source</b>	LED
<b>Work equipment</b>	Electronic plug-in transformer
<b>Connected load</b>	100 - 240 V; AC; 50 Hz; 60 Hz
<b>Power consumption</b>	ca. 6 W
<b>Luminous flux</b>	approx. 420 lm
<b>Luminous efficiency <sup>1)</sup></b>	approx. 70 lm/W
<b>Light type/-color</b>	Cold white
<b>Colour temperatur</b>	approx. 4.000 K
<b>Color rendering index</b>	CRI ≥ 90; R9 ≥ 50
<b>Light distribution</b>	Direct; approx. 100 %
<b>Chromaticity tolerance LED</b>	< 3 SDCM
<b>Glare control</b>	Diffusor
<b>System of protection/Class</b>	IP 20; II
<b>Technology</b>	Continuously dimmable; Touch DIM
<b>Operation</b>	Touch-LED
<b>Housing</b>	Aluminium/plastic; Anodised; Black
<b>Light source cover</b>	Acrylic (PMMA); Satine
<b>Arm</b>	Aluminium coloured anodised
<b>Mains lead</b>	ca. 2,3 m; Mains plug; CEE 7/XVI; BS 1363; NEMA 1-15P
<b>Fastening</b>	Table clamp (accessory); Wall bracket (accessory); Screw-down flange; Magnetic base (accessory)
<b>Lens, dimensions</b>	Ø 72 mm
<b>Diopter lens</b>	6 DPT
<b>EAN</b>	4013330056315
<b>Weight without/incl. packaging</b>	ca. 1,5 kg; 1,8 kg
<b>Packaging dimensions</b>	ca. 980 mm; 200 mm; 130 mm

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear.