


CEE 7/VII



**Light source**

**Work equipment**

**Connected load**

**Secondary tension**

**Power consumption**

**Sec. power consumption**

**Luminous flux**

**Luminous efficiency <sup>1)</sup>**

**Light type/-color**

**Colour temperatur**

**Color rendering index**

**Light distribution**

**Beam angle**

**Chromaticity tolerance LED**

**Luminance (L65)**

**UGR class (4H 8H; EN 12464-1)**

**System of protection/Class**

**Technology**

**Operation**

**Housing**

**Light source cover**

**Mains lead**

**Design**

**Fastening**

**EAN**

**Weight without/incl. packaging**

**Packaging dimensions**

**Special features**

LED

Electronic transformer

100 - 240 V; AC; 50 Hz; 60 Hz

24 V

ca. 23 W

ca. 19 W

approx. 1.400 lm

approx. 73 lm/W

Cold white

approx. 4.000 K

CRI  $\geq$  90; R9  $\geq$  50

Direct; approx. 100 %

110°

< 3 SDCM

$\leq$  23.000 cd/m<sup>2</sup>

$\leq$  28

IP 20; I with plug-in power supply; III without plug-in power supply

Continuously dimmable; Touch DIM

Multi-function switch

Sectional aluminium; Anodised; Aluminium coloured anodised

Polycarbonate (PC); White opal

ca. 4,7 m; Mains plug; CEE 7/VII

Mounted version

Screw-down bracket, horizontal

4013330133832

ca. 1,4 kg; 2,4 kg

ca. 710 mm; 300 mm; 105 mm

Fixed connection

<sup>1)</sup> For luminaires with separate control gear, the luminous efficacy refers to the luminaire head without control gear

